

eNow Rayfrigeration™ Electric TRU Systems

1 eNow Battery Power System

Battery Pack	
Type:	Lithium-ion
Capacity:	124 kW/h
Maximum Battery Charging Power:	Up to 23 kW (varies due to multiple factors)
Ambient Operating Temp Range:	-40C to +60C
Operating Run Time:	8 to 12 hours (determined by various factors including but not limited to ambient temperature, eTRU set point, available solar energy, thermal losses, etc.)

Solar Charging	
Solar Array:	5.8 kW total, 14 individual solar modules (for 53-ft trailer roof)
Modules:	420 watts, .125 thick, flexible, adhesive back permanent mounting, ETFE film coating
Charge controllers:	Maximum Power Point Tracking (MPPT)

Inverter	
AC Output	480 VAC 3-Phase output
	Sine wave filtered with THD less than 5% at full continuous load
	17.5kVA continuous power

Monitoring Systems	
CANBus-based Telemetry System:	Provides detailed information on system operation; includes touch-screen diagnostic/monitoring system
Integrated thermal management system:	Enables operation across wide ambient temperature range
Programmable features:	eTRU start-of-operation for preconditioning trailer ahead of loading

Compliance and Safety	
SAE, IEC, ISO	SAE J1455 Others TBD
Component installation rating	IP67

Specifications subject to change without notice.

Technical Specifications

eNow Rayfrigeration™ Electric TRU Systems

2 Customer-Specified Trailer

Weight	
Overall Trailer Weight:	TBD (based on customer-specified trailer OEM (Great Dane, Hyundai, Utility, Vanguard or Wabash National), performance features and design options)
Weight Variance Provision: Vehicles primarily operated by electric battery-powered engines may exceed weight limit on power unit by up to 2,000 lbs. (up to max. gross vehicle weight of 82,000 lbs.). As outlined in FHWA-DOT guidance. Information: Fixing America's Surface Transportation Act (FAST Act) Truck Size and Weight Provisions	

3 Refrigeration Unit

Reefer Unit	
Electric Only: Carrier Vector™ 8100, single-temp	Weight 1,150 lb. Click to view specs
Hybrid Option: Carrier Vector™ 8500, electric with diesel genset back up, single-temp	Weight 1,875 lb. including fuel tank Click to view specs
Hybrid Option: Carrier Vector™ 8600MT, electric with diesel genset back up, multi-temp	Weight 1,885 lb. including fuel tank Click to view specs

4 eTRU Charging Infrastructure

Shorepower Charging Infrastructure	Level 2/3
Power:	480V 3-Phase via corded connectors
Construction:	Wall-mount or pedestal design; powder-coated stainless steel
Breakaway design:	Reduces impact of accidental drive-off

Specifications subject to change without notice.

